



- Fabricated in accordance with CAN/ULC-S601-14 Standard with ULC label affixed to tank.
- Material - Steel sheet A36 or equal.
- Equipped with I-Beam leg support, Saddle support optional, 2270 Lt & 4540 Lt are equipped with Cradle support.
- Interior of tank as welded.
- Exterior surface blasted in accordance to SSPC-SP6, coated with one coat Epoxy primer & top coat with Urethane paint, other colours available on request.
- Additional fittings available on request.
- Custom fabrication of special sizes.
- Factory air test inspection.
- All Decals bilingual (English & French).
- Installation instruction and warranty documents supply with all tanks.

Part #	Capacity		Dimensions (mm)				Approx. Weight (Kg)
	Litres	Imperial Gallon	A	B	C	D	
95320	2270	500	1270	1295	1800	1825	476
95325	4540	1000	1270	1295	3590	3615	760
95330	9000	1980	1830	1855	3440	3770	2150
95335	10000	2200	1930	1955	3430	3760	2250
95340	13600	2990	1830	1855	5180	5510	2850
95345	15000	3300	1930	1955	5145	5575	2980
95350	22700	4995	2310	2350	5410	5855	4100
95355	25000	5500	2286	2325	6096	6540	4400
95360	35000	7700	2350	2388	8080	8625	5600
95365	45400	9990	3000	3050	6440	7000	7800
95370	50000	11000	3000	3050	7090	7650	8300
95380	75000	16500	3000	3050	10640	11200	11100
953780000	80000	17600	3000	3050	11340	11900	11800